



**PARASNATH ALUMINIUM**

**THINK ALUMINIUM, THINK PARASNATH**

**Phone : +91 9836622666 / 8617263130/ 9331199929 / 9831640153**

**Email : [info@parasnathaluminium.com](mailto:info@parasnathaluminium.com)**



**Corporate Office : "Ecospace Business Tower" Tower 5A, 3rd Floor,  
Suit No.8 , Kolkata-700160.**

**Redg. Office : Ajit Mansion 10/1/1C Kalakar Street, 1st Floor, Kolkata-700007  
Shop Address : 42/1 StrandRoad, Kolkata-700007**

# ALUMINIUM LADDER

## Aluminium Simple Ladder

With corrugated tubular rung pipe steps non-skid rubber shoes and caps.

**ITEM CODE : PA -101**

Specifications :

- 5 ft.
- 6 ft.
- 7 ft.
- 8 ft.
- 9 ft.
- 10 ft.
- 12 ft.
- 14 ft.
- 16 ft.
- 18 ft.
- 20 ft.
- 24 ft.



## Aluminium Self Supporting Ladder

With non slip integrated with steps on the front & non-slip corrugated tube steps on the rear. Hinges support platform at top and non-skid rubber

**ITEM CODE: PA-102**

Specifications :

- 5 ft.
- 6 ft.
- 7 ft.
- 8 ft.
- 9 ft.
- 10 ft.
- 12 ft.
- 14 ft.
- 18 ft.
- 20 ft.
- 24 ft.



## Aluminium Fancy Ladder

Economy self supporting ladder with serrated with step. Foldable platform & non-skid rubber shoes.

**ITEM CODE: PA -103**

Specifications :

- 5 ft.
- 6 ft.
- 7 ft.
- 8 ft.
- 9 ft.
- 10 ft.
- 12 ft.
- 14 ft.
- 16 ft.
- 18 ft.
- 20 ft.
- 24 ft.



## Aluminium Collapsible Ladder

As a rectangular tube when closed & with corrugated range steps opened & with locking clips for closed & open and non-skid rubber shoes and caps.

**ITEM CODE: PA-104**

Specifications :

- 4 ft.
- 5 ft.
- 6 ft.
- 7 ft.
- 8 ft.
- 9 ft.
- 10 ft.
- 12 ft.



## Aluminium Telescopic Folding Step Ladder

Ideal For Cleaning Windows, Interior And Exterior Painting & Decoration, All Other House Hold Works And Office Works Super Quality Alloy Aluminium Built Ladder. Non-Slip Rubber Angled Feet To Protect Floor. Surfaces And Give Great Grip In All Position. Anti-Skid Pvc Shoes For Added Safety.

**ITEM CODE: PA - 105**

Specifications :

- 5 ft.
- 6 ft.
- 7 ft.
- 8 ft.
- 9 ft.
- 10 ft.
- 12 ft.
- 14 ft.
- 16 ft.
- 18 ft.
- 20 ft.
- 24 ft.



## Aluminium Trolley Step Ladder

With wide steps guard rails, platform and attached with 2 non fixed nos swiveling wheel with brake to immobilize the ladder.

**ITEM CODE: PA-106**

Specifications :

- 4 ft.
- 5 ft.
- 6 ft.
- 7 ft.
- 8 ft.
- 9 ft.
- 10 ft.
- 12 ft.



## Aluminium Extension Ladder

Two interlocked simple ladder with corrugated rung step rope pulley & gravity pawls for extending and non-skid rubber shoes caps and hooks at top.

**ITEM CODE: PA- 107**

- Close high 8 ft. When extended 14 ft.
- Close high 10 ft. When extended 18 ft.
- Close high 12 ft. When extended 22 ft.
- Close high 14 ft. When extended 24 ft.
- Close high 16 ft. When extended 28 ft.
- Close high 18 ft. When extended 32 ft.
- Close high 20 ft. When extended 36 ft.
- Close high 24 ft. When extended 40 ft.
- Close high 24 ft. When extended 44 ft.



## Aluminium Self Supporting Extension Ladder

Simple Ladder Fixed With Rote Pulley And Gravity Pawls To extended the simple ladder over the trestle & with non skid rubber shoes

**ITEM CODE: PA-108**

Specifications :

- Close high 8 ft. when extended 14 ft.
- Close high 10 ft. when extended 18 ft.
- Close high 12 ft. when extended 22 ft.
- Close high 14 ft. when extended 24 ft.
- Close high 16 ft. when extended 28 ft.
- Close high 18 ft. when extended 32 ft.
- Close high 20 ft. when extended 36 ft.
- Close high 24 ft. when extended 40 ft.
- Close high 24 ft. when extended 44 ft.



## Aluminum Telescopic Wheeled Ladder

Same as SBA 106 with Extra Side handrail hinged & Safety Self to Extending Part & with Rubber wheels on front legs & non solid Rubber Shoes on Rear Leg & a Push Handle

**ITEM CODE: PA-109**

Specifications :

- Close High 8 ft. when extended 14 ft.
- Close High 10 ft. when extended 18 ft.
- Close High 12 ft. when extended 22 ft.
- Close High 14 ft. when extended 24 ft.
- Close High 16 ft. when extended 28 ft.
- Close High 18 ft. when extended 32 ft.
- Close High 20 ft. when extended 36 ft.
- Close High 24 ft. when extended 40 ft.
- Close High 24 ft. when extended 44 ft.



# ALUMINIUM LADDER

## Aluminum Tower Extension Ladder

With platform, guard rails, tools tray, wire rope pulley, extended by hand winch, mounted on M.S. trolley with a tow bar and with 4 no. caster wheel to moobtee the trolley. The tower also provides with the wire ropes and screw jack to make platform horizontal in slope and to arrest swing of tower.

**ITEM CODE :PA- 110**

Specification:

- Close High 9 ft. when extended 15 ft.
- Close High 11 ft. when extended 19 ft.
- Close High 13 ft. when extended 23 ft.
- Close High 15 ft. when extended 25 ft.
- Close High 17 ft. when extended 29 ft.
- Close High 19 ft. when extended 33 ft.
- Close High 21 ft. when extended 37 ft.
- Close High 25 ft. when extended 41 ft.
- Close High 25 ft. when extended 45 ft.



## Aluminum Tilttable Tower Extension Ladder with JeepTyre

With platform, guard rates, tools tray, wire rope pulley, extended by hand winch,mounted of Heavy Duty M.S. trolley with a tow bar and with 4 no. Zeep TYRE to mobilize the trolley, to tilt it from vertical to horizontal by winch gear. The tower also provides with the wire ropes and screw jack to make platform horizontal in slope and to arrest swing of tower.

**ITEM CODE :PA- 112**

Specification

- Close High 9 ft. when extended 15 ft.
- Close High 9 ft. when extended 15 ft.
- Close High 13 ft. when extended 23 ft.
- Close High 15 ft. when extended 25 ft.
- Close High 17 ft. when extended 29 ft.
- Close High 19 ft. when extended 33 ft.
- Close High 21 ft. when extended 37 ft.
- Close High 25 ft. when extended 41 ft.
- Close High 9 ft. when extended 45 ft.



## Aluminum Rope Ladder

With sides of Quality Nylon Rope and steps of 25.4 mm dia fluted aluminum tube in required length, can be rolled in a small bunches for easy handling, storage and transportation.



**ITEM CODE : PS- 113**

**Key Specifications**

- **Material: High-Grade Aluminium Alloy**
- **Type: Self Support / A-Type Ladder**
- **Load Capacity: 100 kg - 150 kg (depending on model)**
- **Available Heights: 4 ft, 6 ft, 8 ft, 10 ft, 12 ft, and customized sizes**
- **Step Width: 75 mm - 100 mm**
- **Step Type: Anti-slip corrugated steps**
- **Frame Thickness: Heavy-duty aluminium section**
- **Finish: Natural Aluminium / Anodized Finish**
- **Safety Features: Non-slip rubber shoes, sturdy locking mechanism, reinforced platform**
- **Weight: Lightweight for easy portability**
- **Corrosion Resistance: Excellent resistance to rust and weather conditions**

**Aluminium Self Support Ladder**

## Aluminum Tilttable Tower Extension Ladder

With platform, guard rails, tools tray, wire rope pulley, extended by hand hinch, mounted on M.S. trolley with a tow bar and with 4 no. caster wheel to mobilize the trolley, to fit it from vertical to horizontal by winch gear. The tower also provides with the wire ropes and screw jack to make platform horizontal in slope and to arrest swing of tower.

**ITEM CODE: PA-111**

Specification :


- Close High 9 ft. when extended 15 ft.
- Close High 11 ft. when extended 19 ft.
- Close High 13 ft. when extended 23 ft.
- Close High 15 ft. when extended 25 ft.
- Close High 17 ft. when extended 29 ft.
- Close High 19 ft. when extended 33 ft.
- Close High 21 ft. when extended 37 ft.
- Close High 21 ft. when extended 41 ft.
- Close High 25 ft. when extended 41 ft.
- Close High 25 ft. when extended 45 ft.



## Technical Specifications

- Material Construction: High-grade aluminium alloy (lightweight & corrosion-resistant)
- Ladder Type: Mobile Scaffold Ladder / Folding Scaffold Ladder / Fixed Frame
- Height Range: 6 ft to 40 ft (customizable as per requirement)
- Platform Height: 4 ft to 30 ft
- Load Capacity: 150 kg to 300 kg
- Pipe Diameter: 40 mm to 50 mm
- Wall Thickness: 1.2 mm to 3 mm
- Platform Size: 1.2 m x 0.6 m (custom sizes available)
- Platform Material: Anti-slip aluminium / wooden board with aluminium frame
- No. of Steps/Rungs: 6 to 20 (depending on height)
- Rung Spacing: 10 to 12 inches
- Mobility: Heavy-duty caster wheels with locking system
- Safety Features: Guard rails, anti-slip steps, stabilizers, locking pins
- Surface Finish: Anodized / Mill finish
- Assembly Type: Knock-down / Modular design
- Usage Type: Indoor & outdoor industrial use
- Compliance: Designed as per industrial safety standards

## Aluminium Scaffold Ladder



## Technical Specifications

- Material Construction: High-strength aluminium alloy / Mild steel (optional)
- Ladder Type: Self-Support (A-Type) Platform Ladder
- Height Range: 4 ft to 20 ft (custom sizes available)
- Platform Height: 3 ft to 18 ft
- Load Capacity: 120 kg to 250 kg
- Frame Structure: Double-side support with rigid locking system
- Step Type: Anti-slip wide steps
- Step Width: 3 inch to 6 inch
- Rung Spacing: 10 to 12 inches
- Top Platform Size: 400 mm x 400 mm (customizable)
- Platform Type: Anti-skid aluminium / MS platform
- Handrails: Provided on both sides for safety
- Base Support: Rubber shoes / anti-skid feet
- Mobility (Optional): Caster wheels with brake locking system
- Finish: Anodized aluminium / Powder-coated MS
- Folding Type: Foldable / Non-foldable options available
- Stability Feature: Back support frame for self-balancing
- Usage Type: Indoor & outdoor industrial / commercial use
- Compliance: Designed as per industrial safety standards

## Self Support Platform Ladder



# OUR MORE VARIETY OF LADDER



# OUR MORE VARIETY OF LADDER



# CONTACT US



+91 9836622666 / 8617263130 /  
+91 9331199929 / 9831640153



[info@parasnathaluminium.com](mailto:info@parasnathaluminium.com)



**Factory Address:** “Uttsav Park“, Dulagarh, Village & P.O. Chaturbhuji Kathi,  
P.S - Sankrail, Para - Hudati Para, Plot No. 55 Phase - 1, Howrah - 711303



**Redg. Office:** “Ajit Mansion“ 10/1/1C  
Kalakar Street, 1st Floor, Kolkata-700007



**Corporate Office:** “Ecospace Business Tower  
5A”, 3rd Floor, Suite No. 8, Kolkata-700160



**Shop Address:** 42/1 Strand Road, Kolkata-700007



[www.parsnathaluminium.com](http://www.parsnathaluminium.com)

